



# Lifelong Worldwide Bowling

## Ball Accelerator Instructions



1) Remove the bottom two bolts from the upper support

2) Use the longer bolts provided and attach the Ball Accelerator support to the ball lift tube as shown. Be sure the support is against the tube when tightened down. The unit was shipped to you with the support bracket reversed on the ball accelerator from the actual mounting position for packaging purposes.



[www.bowlingproducts.com](http://www.bowlingproducts.com)  
[lifelong@bowlingproducts.com](mailto:lifelong@bowlingproducts.com)  
727-378-5884



# Lifelong Worldwide Bowling

## Ball Accelerator Instructions



3) Slip the Ball Accelerator between the belt and the tube of the ball lift above the support bracket you just mounted. The long wheeled section goes downward toward the bottom pulley. Slide the Ball Accelerator down to the mounting tabs while flexing the ball lift belt down to line the bolts up with the Ball Accelerator tabs. Clamp it down with the provided mounting tabs and nuts. The units wheels will be around an inch from the bottom of the belt.

### Shock Absorber

If you're installing the Gripper Belt at this time or whenever be sure you have a proper working shock absorber. The correct shock should have more resistance as the lift rises and less resistance while coming down. If the shock is too stiff coming down it will lower slower and may allow the actuating pads of the gripper belt to skip from one hump to the other reducing its operating affect.

www.bowlingproducts.com  
lifelong@bowlingproducts.com  
727-378-5884



# Lifelong Worldwide Bowling

## Ball Accelerator Instructions



The Gripper Belt has a ten year pro-rated warranty and is very strong. Feel free if needed to add extra downward pressure with an additional spring going across the tube of the lift. That's your discretion.

www.bowlingproducts.com  
lifelong@bowlingproducts.com  
727-378-5884